


DRAWING FOR CUSTOMER



■SPEC.:

- Rated Voltage:100V AC,DC
- Rated Current:2A AC,DC(AWG24#)
- Withstand Voltage:500V AC/minute
- Contact Resistance:20mΩ max
- Insulation Resistance:500MΩ min
- Temperature Range:-25℃~+85℃

■Terminal:

- Material:Phosphor Bronze
- Finish:Tin-plated,over Nickel
- Applicable wire:AWG#24~28

XY15001-X X T 2 A

1:All plated
2:Half plated


Version

Plating


0: Tin-plat
1: Gold Flash
2: Gold Plat3u"
3: Gold Plat5u"

Mold No.

Terminal



Section:B-B



Section:A-A

XYCO 东莞市轩业电子科技有限公司
TEL: 0769-8297 9981 <http://www.XYCO.com.cn>

					TOLERANCE 公 差	DRAWING 設計者	Devin	XY15001-XXT2A		XYCO 东莞市軒並電子科技有限公司 TEL: 0769-8297 9981 http://www.XYCO.com.cn			
2021-03-17	A		XY15001-XXT2A	Devin	.X=±0.30 .XX=±0.20 .XXX=±0.10	CHECKED 審查	Leo Li	PART NO. 料號		UNIT 單位	mm	PRODUCT NAME 產品名稱	ZE PH1.50mm Wire To Board Terminal
DATE 日期	VER 版本		CHANGE HISTORY 變更歷史	CHANGED NAME 修改後料號	DRAWING 變更者	APPROVED 核准	William	DWG NO. 圖號	PE210908A				